



SC04_V

common mode inductors

– noise suppression


VDE 565-2




SC series conform to VDE 565-2. They have copper winding on ferrite toroid in epoxy case. Phase opposition winding is an excellent filter for symmetrical noise and in association with capacitors to ground it filters asymmetrical noise.

Main use is switching power supplies.


SC04 V



SC04 H



ELECTRICAL DIAGRAM



Dimensions in mm

SPECIFICATIONS

MECHANICAL

TOROID... ferrite
CASE... plastic

ENVIRONMENTAL

OPERATING TEMPERATURE
RANGE... -40°C +125°C

ELECTRICAL

NOMINAL OPERATING VOLTAGE... 250 V RMS
LIMITING VOLTAGE... 1500 V RMS 50 Hz

by winding

Nominal current A	Inductance mH	DCR max. mΩ
0,3	47	2600
0,4	33	1800
0,7	18	1000
1	10	540
1,1	6,8	450
1,3	4,7	320
1,7	3,3	200
3	1	56
5	0,47	30

Other values on request.


MARKING

Printed in clear : Manufacturer, series, model, inductance value, nominal current by winding, nominal operating voltage, diagram windings.

PACKAGING

50 pieces in waffle pack.

ORDERING PROCEDURE



VISHAY S.A.
Division Aztronic
Z.I. de Bellitourne
BP 353 - AZE
53203 Château-Gontier Cedex
Tél (33) 02 43 09 51 10
Fax (33) 02 43 07 36 43